




# EC PACK INDUSTRIAL LIMITED

Flat A, 4/F, Valiant Commercial Building, No. 22-24 Prat Avenue, T.S.T., Kowloon, Hong Kong  
Tel: (852) 2957 8208 Fax: (852) 2957 8202 E-Mail: hk@ec-packing.com

## Spray Valve (Non- Pressurize) Specification

**Item Code: APU-0C12-G1**

Product Structure	
Component	Part Description
1. Insert	POM, MBU, plane
2. Actuator	PP, assembled with insert
3. Up piston	POM (Natural)
4. Inner Gasket	Rubber
5. Outer Gasket	Rubber
6. Collar	PE
7. Mounting cup	Fe, Both-side lacquered tinplate
8. Spring	Stainless Steel
9. Lower piston	PE (Natural)
10. Stem insert	PE (Natural)
11. Spring	Stainless Steel
12. Housing	PP (Natural)
13. Matting	PE (Natural)
14. Ball	Glass
15. Diptube	PE (Natural)



**Dosage = 0.12ml ±0.02 ml**  
**Prime strokes = 3-5 times**  
**Weight (Without Diptube) = 7.0±0.2 g**

Remarks: This aerosol valve specification has been designed and developed for a particular formulation and spray characteristic only. Any changes in propellants, actives, solvents, fragrances or any other product ingredients may make this valve non compatible or unsuitable EC Pack endeavours to provide the most appropriate aerosol valve specifications to the users, but has no responsibility and control over its final application. Users of this valve specification are responsible for testing its compatibility and suitability.